

Alu Heizkörper Wärmeleistungstabellen

VL 40°C / RL 30°C / RT 20°C [Watt]																			
Glieder	Baulänge mit Hauben	V250/60	V350/60	V500/60	V600/60	V900/60	V1800/60	V250/130	V350/130	V500/130	V600/130	V900/130	V1800/130	V250/200	V350/200	V500/200	V600/200	V900/200	V1800/200
3	330	32	40	55	64	90	166	57	71	98	113	161	296	89	111	141	163	231	425
4	400	43	53	74	85	121	222	76	95	131	151	214	395	118	148	189	217	308	567
5	470	53	67	92	106	151	277	95	119	164	189	268	493	148	184	236	272	385	709
6	540	64	80	111	127	181	333	114	143	197	227	322	592	177	221	283	326	462	851
7	610	75	94	129	149	211	388	133	166	230	264	375	690	207	258	330	380	539	993
8	680	86	107	148	170	241	443	152	190	263	302	429	789	236	295	377	434	617	1.135
9	750	96	120	166	191	271	499	171	214	295	340	482	888	266	332	424	489	694	1.276
10	820	107	134	185	212	301	554	190	238	328	378	536	986	295	369	472	543	771	1.418
11	890	118	147	203	233	332	610	209	262	361	415	590	1.085	325	406	519	597	848	
12	960	128	160	222	255	362	665	228	285	394	453	643	1.184	354	443	566	652	925	
13	1.030	139	174	240	276	392	721	248	309	427	491	697		384	479	613	706	1.002	
14	1.100	150	187	258	297	422	776	267	333	459	529	750		413	516	660	760	1.079	
15	1.170	160	200	277	318	452	831	286	357	492	566	804		443	553	707	815	1.156	
16	1.240	171	214	295	340	482	887	305	380	525	604	858		472	590	755	869	1.233	
17	1.310	182	227	314	361	512	942	324	404	558	642	911		502	627	802	923	1.310	
18	1.380	193	241	332	382	543	998	343	428	591	680	965		531	664	849	977	1.387	
19	1.450	203	254	351	403	573	1.053	362	452	623	718	1.019		561	701	896	1.032	1.464	
20	1.520	214	267	369	425	603	1.109	381	475	656	755	1.072		590	738	943	1.086		
21	1.590	225	281	388	446	633	1.164	400	499	689	793	1.126		620	774	990	1.140		
22	1.660	235	294	406	467	663	1.220	419	523	722	831	1.179		649	811	1.038	1.195		
23	1.730	246	307	425	488	693	1.275	438	547	755	869	1.233		679	848	1.085	1.249		
24	1.800	257	321	443	509	723	1.330	457	571	788	906	1.287		708	885	1.132	1.303		
25	1.870	267	334	462	531	754		476	594	820	944	1.340		738	922	1.179	1.358		
26	1.940	278	348	480	552	784		495	618	853	982	1.394		768	959	1.226	1.412		
27	2.010	289	361	498	573	814		514	642	886	1.020	1.447		797	996	1.273	1.466		
28	2.080	300	374	517	594	844		533	666	919	1.057	1.501		827	1.033	1.321	1.520		
29	2.150	310	388	535	616	874		552	689	952	1.095			856	1.069	1.368	1.575		
30	2.220	321	401	554	637	904		571	713	984	1.133			886	1.106	1.415	1.629		
31	2.290	332	414	572	658	934		590	737	1.017	1.171			915	1.143	1.462	1.683		
32	2.360	342	428	591	679	965		609	761	1.050	1.208			945	1.180	1.509	1.738		

Andere Vorlauf- / Rücklaufraumtemperaturen finden Sie unter www.olymp.at